Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-074-6222

| Vibration Resistance Range In Hertz: | |
|---|--|
| Not rated | |
| Shock Resistance Rating In Gravitational Units: | |
| Not rated | |
| Operating Tempurature Range: | |
| -25.0/+71.0 degrees celsius | |
| Average Life Measurement: | |
| Not rated | |
| Basic Shape Style: | |
| Rectangular or square | |
| Identification Designator: | |
| Sm-a-934937-80063 | |
| Maximum Operating Altitude Rating: | |
| 50000.0 feet | |
| Inclosure Type: | |
| Encased | |
| Installation Design: | |
| Drawer | |
| Circuit Construction Type: | |
| Solid state | |
| Frequency Per Channel: | |
| Not rated | |
| Attenuation In Decibels: | |
| 90.0 | |
| Average Power Rating Per Channel: | |
| Not rated | |
| Signal Voltage Rating Per Channel: | |
| 24.000 volts input | |
| Overall Gain: | |
| 10.0 decibels | |
| Impedance Rating Per Channel: | |
| 180.000 ohms input channel err-100 | |
| Distortion Type And Percent: | |
| 10.0 frequency | |
| Maximum Continuous Operating Time In Hours: | |
| Not rated | |
| Connection Type And Location: | |
| Integral cord w/power plug front | |
| External Dc Operating Voltage In Volts: | |
| 24.0 single voltage | |
| Shelf Life: | |
| N/a | |
| | |

Crystal Controlled Oscillator - Page 2 of 2



Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32200