

NSN 5955-01-079-9198 Noncrystal Controlled Oscillator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5955-01-079-9198 **Overall Length:** 0.800 inches **Overall Height:** 0.565 inches **Overall Width:** 0.500 inches **Environmental Protection:** Moisture proof and shock resistant and vibration **Vibration Resistance Range In Hertz:** +10.0/+55.0 **Vibration Resistance Amplitude:** 0.06 inches total excursion **Shock Resistance Rating In Gravitational Units:** 30.0 **Operating Tempurature Range:** -55.0/+85.0 degrees celsius **Storage Tempurature Range:** -62.0/+125.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Identification Designator:** 210-101-01-99592 **Inclosure Type:** Encased **Operating Control Method:** Automatic

Installation Design:

Module

Control Type:

Remote

Circuit Construction Type:

Solid state

Frequency Per Channel:

4.0 megahertz operating channel

Shock Pulse Duration Time:

11.0 milliseconds

Connection Type And Location:

Pin bottom

Connection Contact Type And Quantity:

7 pin external

NSN 5955-01-079-9198

Noncrystal Controlled Oscillator - Page 2 of 2



External Dc	Operating	Voltage I	n Volts:

4.75 single voltage and 5.25 single voltage

Precious Material And Location:

Pin surfaces gold

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A32200