NSN 5955-01-087-2312

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-087-2312 **Overall Length:** 0.780 inches **Overall Height:** 0.640 inches **Overall Width:** 0.490 inches **Environmental Protection:** Shock resistant and vibration **Operating Tempurature Range:** -25.0/+125.0 degrees celsius **Storage Tempurature Range:** -25.0/+75.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Identification Designator:** L14e-g4mhz-21022 **Inclosure Type:** Hermetically sealed Installation Design: Module **Circuit Construction Type:** Solid state **Frequency Per Channel:** 4.0 megahertz output channel **Average Power Rating Per Channel:** 200.0 milliwatts output **Signal Voltage Rating Per Channel:** 0.400 volts output and 2.400 volts output **Connection Type And Location:** Printed circuit bottom **Connection Contact Type And Quantity:** 14 printed circuit external **External Dc Operating Voltage In Volts:** 5.0 single voltage Monolithic and positive outputs and medium speed

Special Features: Precious Material And Location: Terminal surfaces gold **Precious Material:** Gold

NSN 5955-01-087-2312

Crystal Controlled Oscillator - Page 2 of 2



Test Data Document:

81755-c10619 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A32200