## NSN 5955-01-094-9068

Noncrystal Controlled Oscillator - Page 1 of 2



,
View Online at https://aerobasegroup.com/nsn/5955-01-094-9068
Overall Length:
0.790 inches
Overall Height:
Between 0.160 inches and 0.190 inches
Overall Width:
0.490 inches
Environmental Protection:
Shock resistant and vibration
Operating Tempurature Range:
-30.0/+85.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Average Life Measurement:
Not rated
Basic Shape Style:
Rectangular or square
Identification Designator:
5413-20m-08111
Inclosure Type:
Hermetically sealed
Operating Control Method:
Manual
Installation Design:
Module
Control Type:
Local
Circuit Construction Type:
Solid state
Frequency Per Channel:
20.0 megahertz output channel
Signal Voltage Rating Per Channel:
0.400 volts output and 2.400 volts output
Overall Gain:
50.0 milliamperes

**Connection Type And Location:** 

Printed circuit bottom

**Connection Contact Type And Quantity:** 

14 printed circuit external

**External Dc Operating Voltage In Volts:** 

5.0 single voltage

Special Features:

Monolithic and positive outputs

## NSN 5955-01-094-9068

Noncrystal Controlled Oscillator - Page 2 of 2



## **Test Data Document:**

27963-85765500 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A32200