## NSN 5955-01-096-4760

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-096-4760

Overall Length:
0.778 inches
Terminal Length:
Between 0.223 inches and 0.248 inches
Overall Width:
0.435 inches
Body Length:
0.530 inches
Body Width:
0.402 inches
Body Thickness:
0.150 inches
Overall Thickness:
0.183 inches
Terminal Diameter:
0.040 inches
Mode Of Oscillation:
Fifth overtone and third overtone
Circuit Resonance:
Series resonance
Shunt Capacitance In Picofarads:
7.0
Specified Frequency:
111.200 megahertz
Holder Cover Material:
Metal
Operating Tempurature Range:
-40.0/+90.0 degrees celsius and -55.0/+105.0 degrees celsius
Center To Center Distance Between Terminals:
0.192 inches
Drive Level Rating:
Between 2.0 milliwatts and 1.6 milliwatts and 2.4 milliwatts
Frequency Tolerance For Operating Tempurature In Percent:
-0.002/+0.002 and -0.003/+0.003
Equivalent Resistance Value In Ohms:
60.0
Special Features:
The pin undercut may be omitted
Style Designator:
7 pin tube base
Test Data Document:

81349-mil-c-3098/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## NSN 5955-01-096-4760

Quartz Crystal Unit - Page 2 of 2



Spec	ifica	tion	Data:
------	-------	------	-------

81349-mil-c-3098/60 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A059a0