NSN 5955-01-100-0724

Quartz Crystal Unit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5955-01-100-0724

Overall Length:
Between 0.600 inches and 0.650 inches
Terminal Length:
1.000 inches
Overall Width:
Between 0.500 inches and 0.565 inches
Overall Thickness:
0.238 inches
Terminal Diameter:
Between 0.015 inches and 0.032 inches
Mode Of Oscillation:
Fundamental
Circuit Resonance:
Antiresonance
Load Capacitance In Picofarads:
Between 32.0 and 31.5 and 32.5
Specified Frequency:
2.458 megahertz
Holder Cover Material:
Holder Cover Material: Metal
Metal
Metal Operating Tempurature Range:
Metal Operating Tempurature Range: +0.0/+70.0 degrees celsius
Metal Operating Tempurature Range: +0.0/+70.0 degrees celsius Center To Center Distance Between Terminals:
Metal Operating Tempurature Range: +0.0/+70.0 degrees celsius Center To Center Distance Between Terminals: 0.265 mils and 0.290 centimeters
Metal Operating Tempurature Range: +0.0/+70.0 degrees celsius Center To Center Distance Between Terminals: 0.265 mils and 0.290 centimeters Frequency Tolerance For Operating Tempurature In Percent:
Metal Operating Tempurature Range: +0.0/+70.0 degrees celsius Center To Center Distance Between Terminals: 0.265 mils and 0.290 centimeters Frequency Tolerance For Operating Tempurature In Percent: -0.005/+0.005
Metal Operating Tempurature Range: +0.0/+70.0 degrees celsius Center To Center Distance Between Terminals: 0.265 mils and 0.290 centimeters Frequency Tolerance For Operating Tempurature In Percent: -0.005/+0.005 Equivalent Resistance Value In Ohms:
Metal Operating Tempurature Range: +0.0/+70.0 degrees celsius Center To Center Distance Between Terminals: 0.265 mils and 0.290 centimeters Frequency Tolerance For Operating Tempurature In Percent: -0.005/+0.005 Equivalent Resistance Value In Ohms: 250.0
Metal Operating Tempurature Range: +0.0/+70.0 degrees celsius Center To Center Distance Between Terminals: 0.265 mils and 0.290 centimeters Frequency Tolerance For Operating Tempurature In Percent: -0.005/+0.005 Equivalent Resistance Value In Ohms: 250.0 Style Designator:
Metal Operating Tempurature Range: +0.0/+70.0 degrees celsius Center To Center Distance Between Terminals: 0.265 mils and 0.290 centimeters Frequency Tolerance For Operating Tempurature In Percent: -0.005/+0.005 Equivalent Resistance Value In Ohms: 250.0 Style Designator: Oval body, pin terminals
Metal Operating Tempurature Range: +0.0/+70.0 degrees celsius Center To Center Distance Between Terminals: 0.265 mils and 0.290 centimeters Frequency Tolerance For Operating Tempurature In Percent: -0.005/+0.005 Equivalent Resistance Value In Ohms: 250.0 Style Designator: Oval body, pin terminals Shelf Life:
Metal Operating Tempurature Range: +0.0/+70.0 degrees celsius Center To Center Distance Between Terminals: 0.265 mils and 0.290 centimeters Frequency Tolerance For Operating Tempurature In Percent: -0.005/+0.005 Equivalent Resistance Value In Ohms: 250.0 Style Designator: Oval body, pin terminals Shelf Life: N/a
Metal Operating Tempurature Range: +0.0/+70.0 degrees celsius Center To Center Distance Between Terminals: 0.265 mils and 0.290 centimeters Frequency Tolerance For Operating Tempurature In Percent: -0.005/+0.005 Equivalent Resistance Value In Ohms: 250.0 Style Designator: Oval body, pin terminals Shelf Life: N/a
Metal Operating Tempurature Range: +0.0/+70.0 degrees celsius Center To Center Distance Between Terminals: 0.265 mils and 0.290 centimeters Frequency Tolerance For Operating Tempurature In Percent: -0.005/+0.005 Equivalent Resistance Value In Ohms: 250.0 Style Designator: Oval body, pin terminals Shelf Life: N/a Unit Of Measure:

A059a0