

View Online at <https://aerobasegroup.com/nsn/5955-01-102-5686>

**Overall Length:**

0.259 inches

**Terminal Length:**

0.660 inches

**Diameter:**

0.318 inches

**Overall Diameter:**

0.408 inches

**Terminal Diameter:**

0.018 inches

**Mode Of Oscillation:**

Fundamental

**Circuit Resonance:**

Antiresonance

**Load Capacitance In Picofarads:**

30.0

**Shunt Capacitance In Picofarads:**

7.0

**Specified Frequency:**

18.000 megahertz

**Holder Cover Material:**

Metal

**Operating Temperature Range:**

-55.0/+105.0 degrees celsius

**Center To Center Distance Between Terminals:**

0.200 inches

**Drive Level Rating:**

Between 4.0 milliwatts and 6.0 milliwatts

**Frequency Tolerance For Operating Temperature In Percent:**

-0.005/+0.005

**Equivalent Resistance Value In Ohms:**

25.0

**Style Designator:**

Hat type, 3 wire leads

**Test Data Document:**

81349-mil-c-3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-c-3098/103 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A059a0