NSN 5955-01-107-3688

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-107-3688

Overall Length:
1.023 inches
Terminal Length:
Between 0.223 inches and 0.248 inches
Overall Width:
0.757 inches
Body Length:
0.775 inches
Body Width:
0.725 inches
Body Thickness:
0.317 inches
Overall Thickness:
0.352 inches
Terminal Diameter:
0.050 inches
Mode Of Oscillation:
Third overtone
Circuit Resonance:
Series resonance
Shunt Capacitance In Picofarads:
7.0
Specified Frequency:
41.035714 megahertz
41.035714 megahertz Frequency Tolerance At Reference Tempurature In Percent:
•
Frequency Tolerance At Reference Tempurature In Percent:
Frequency Tolerance At Reference Tempurature In Percent: -0.007/+0.007
Frequency Tolerance At Reference Tempurature In Percent: -0.007/+0.007 Frequency Stability In Percent:
Frequency Tolerance At Reference Tempurature In Percent: -0.007/+0.007 Frequency Stability In Percent: -0.0025/+0.0025
Frequency Tolerance At Reference Tempurature In Percent: -0.007/+0.007 Frequency Stability In Percent: -0.0025/+0.0025 Controlled Reference Temp:
Frequency Tolerance At Reference Tempurature In Percent: -0.007/+0.007 Frequency Stability In Percent: -0.0025/+0.0025 Controlled Reference Temp: 85.0 degrees celsius
Frequency Tolerance At Reference Tempurature In Percent: -0.007/+0.007 Frequency Stability In Percent: -0.0025/+0.0025 Controlled Reference Temp: 85.0 degrees celsius Operable Tempurature Range:
Frequency Tolerance At Reference Tempurature In Percent: -0.007/+0.007 Frequency Stability In Percent: -0.0025/+0.0025 Controlled Reference Temp: 85.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius
Frequency Tolerance At Reference Tempurature In Percent: -0.007/+0.007 Frequency Stability In Percent: -0.0025/+0.0025 Controlled Reference Temp: 85.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius Holder Cover Material:
Frequency Tolerance At Reference Tempurature In Percent: -0.007/+0.007 Frequency Stability In Percent: -0.0025/+0.0025 Controlled Reference Temp: 85.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius Holder Cover Material: Metal
Frequency Tolerance At Reference Tempurature In Percent: -0.007/+0.007 Frequency Stability In Percent: -0.0025/+0.0025 Controlled Reference Temp: 85.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius Holder Cover Material: Metal Operating Tempurature Range:
Frequency Tolerance At Reference Tempurature In Percent: -0.007/+0.007 Frequency Stability In Percent: -0.0025/+0.0025 Controlled Reference Temp: 85.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius Holder Cover Material: Metal Operating Tempurature Range: +70.0/+80.0 degrees celsius
Frequency Tolerance At Reference Tempurature In Percent: -0.007/+0.007 Frequency Stability In Percent: -0.0025/+0.0025 Controlled Reference Temp: 85.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius Holder Cover Material: Metal Operating Tempurature Range: +70.0/+80.0 degrees celsius Center To Center Distance Between Terminals:
Frequency Tolerance At Reference Tempurature In Percent: -0.007/+0.007 Frequency Stability In Percent: -0.0025/+0.0025 Controlled Reference Temp: 85.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius Holder Cover Material: Metal Operating Tempurature Range: +70.0/+80.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches

-0.001/+0.001

NSN 5955-01-107-3688

Quartz Crystal Unit - Page 2 of 2



Equivalent Resistance	Value In	Ohms:
------------------------------	----------	-------

40.0

Style Designator:

Oval body, pin terminals

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A059a0