NSN 5955-01-107-3695

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-107-3695

| Overall Length: | | |
|---|--|--|
| 1.023 inches | | |
| Terminal Length: | | |
| Between 0.223 inches and 0.248 inches | | |
| Overall Width: | | |
| 0.757 inches | | |
| Body Length: | | |
| 0.775 inches | | |
| Body Width: | | |
| 0.725 inches | | |
| Body Thickness: | | |
| 0.317 inches | | |
| Overall Thickness: | | |
| 0.352 inches | | |
| Terminal Diameter: | | |
| 0.050 inches | | |
| Mode Of Oscillation: | | |
| Third overtone | | |
| Circuit Resonance: | | |
| Series resonance | | |
| Shunt Capacitance In Picofarads: | | |
| 7.0 | | |
| Specified Frequency: | | |
| 43.125000 megahertz | | |
| Frequency Tolerance At Reference Tempurature In Percent: | | |
| -0.007/+0.007 | | |
| Frequency Stability In Percent: | | |
| -0.0025/+0.0025 | | |
| Controlled Reference Temp: | | |
| 85.0 degrees celsius | | |
| Operable Tempurature Range: | | |
| -55.0/+90.0 degrees celsius | | |
| Holder Cover Material: | | |
| Metal | | |
| Operating Tempurature Range: | | |
| +70.0/+80.0 degrees celsius | | |
| Center To Center Distance Between Terminals: | | |
| 0.486 inches | | |
| Drive Level Rating: | | |
| Between 0.8 milliwatts and 1.2 milliwatts | | |
| Frequency Tolerance For Operating Tempurature In Percent: | | |

-0.001/+0.001

NSN 5955-01-107-3695

Quartz Crystal Unit - Page 2 of 2



| Equivalent Resistance | Value In | Ohms: |
|-----------------------|----------|-------|
|-----------------------|----------|-------|

40.0

Style Designator:

Oval body, pin terminals

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A059a0