

View Online at <https://aerobasegroup.com/nsn/5955-01-109-4220>

Overall Length:

0.815 inches

Overall Height:

0.200 inches

Overall Width:

0.515 inches

Environmental Protection:

Moisture proof and shock resistant and vibration

Vibration Resistance Range In Hertz:

+55.0/+2000.0

Vibration Resistance Amplitude:

35.0 gravitational units

Shock Resistance Rating In Gravitational Units:

100.0

Operating Temperature Range:

+0.0/+70.0 degrees celsius

Cubic Measure:

0.080 cubic inches

Storage Temperature Range:

-55.0/+125.0 degrees celsius

Average Life Measurement:

Not rated

Basic Shape Style:

Rectangular or square

Identification Designator:

X0-33-d-8-91637

Inclosure Type:

Hermetically sealed

Operating Control Method:

Automatic

Installation Design:

Module

Control Type:

Local

Storage Type:

Any acceptable

Circuit Construction Type:

Solid state

Frequency Per Channel:

8.0 megahertz output channel

Distortion Type And Percent:

1.0 frequency

Shock Pulse Duration Time:

100.0 microseconds

Connection Type And Location:

Printed circuit bottom

Connection Contact Type And Quantity:

4 printed circuit external

External Dc Operating Voltage In Volts:

5.0 single voltage

Features Provided:

Automatic gain control

Precious Material And Location:

Terminal surface gold

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A32200