

NSN 5955-01-110-7268 Noncrystal Controlled Oscillator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5955-01-110-7268 **Overall Length:** 2.000 inches **Overall Height:** Any acceptable **Overall Width:** 2.000 inches **Individual Section Quantity: Operating Tempurature Range:** -54.0/+75.0 degrees celsius **Average Life Rating:** 75000.0 **Average Life Measurement: Average Life Rating In Hours:** 75000.0 **Basic Shape Style:** Rectangular or square **Identification Designator:** A98-21439-01238 Inclosure Type: Encased

Installation Design:

Panel

Circuit Construction Type:

Any acceptable

Frequency Per Channel:

428.0 megahertz output channel and 538.0 megahertz output channel

Variation Frequency Rating In Decibels:

3.0

Average Power Rating Per Channel:

5.0 milliwatts output

Signal Voltage Rating Per Channel:

18.000 volts input

Impedance Rating Per Channel:

4.700 kilohms operating channel

Connection Type And Location:

Receptacle, coaxial top and solder lug top

Connection Contact Type And Quantity:

3 pressurized coaxial socket internal and 2 solder lug external

Shelf Life:

N/a

NSN 5955-01-110-7268

Noncrystal Controlled Oscillator - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A32200