

View Online at <https://aerobasegroup.com/nsn/5955-01-110-9921>

Overall Length:

0.815 inches

Overall Height:

0.425 inches

Overall Width:

0.515 inches

Environmental Protection:

Shock resistant and vibration

Vibration Resistance Range In Hertz:

+55.0/+2000.0

Vibration Resistance Amplitude:

35.0 gravitational units

Shock Resistance Rating In Gravitational Units:

1000.0

Operating Temperature Range:

-0.0/+70.0 degrees celsius

Average Life Measurement:

Not rated

Basic Shape Style:

Rectangular or square

Identification Designator:

K1100a-04713

Inclosure Type:

Encased

Installation Design:

Module

Circuit Construction Type:

Any acceptable

Frequency Per Channel:

8.448 megahertz operating channel

Signal Voltage Rating Per Channel:

5.000 volts input

Shock Pulse Duration Time:

0.35 milliseconds

Connection Type And Location:

Solder lug bottom

Connection Contact Type And Quantity:

4 solder lug external

External Dc Operating Voltage In Volts:

5.0 single voltage

Precious Material And Location:

Pin surfaces gold

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A32200