## NSN 5955-01-110-9922

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-110-9922 **Overall Length:** 0.815 inches **Overall Height:** 0.425 inches **Overall Width:** 0.515 inches **Environmental Protection:** Shock resistant and vibration **Vibration Resistance Range In Hertz:** +55.0/+2000.0 **Vibration Resistance Amplitude:** 35.0 gravitational units **Shock Resistance Rating In Gravitational Units:** 1000.0 **Operating Tempurature Range:** -0.0/+70.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Identification Designator:** K1100a-04713 **Inclosure Type:** Encased **Installation Design:** Module **Circuit Construction Type:** Any acceptable Frequency Per Channel: 10.000 megahertz operating channel Signal Voltage Rating Per Channel: 5.000 volts input **Shock Pulse Duration Time:** 

Shock Pulse Duration Time:

0.35 milliseconds

Connection Type And Location:

Solder lug bottom

Connection Contact Type And Quantity:

4 solder lug external

External Dc Operating Voltage In Volts:

5.0 single voltage

Precious Material And Location:

Pin surfaces gold

## NSN 5955-01-110-9922

Crystal Controlled Oscillator - Page 2 of 2



Precious Mate	rıaı	l:
---------------	------	----

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200