Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-110-9923

Overall Length:
0.815 inches
Overall Height:
0.425 inches
Overall Width:
0.515 inches
Environmental Protection:
Shock resistant and vibration
Vibration Resistance Range In Hertz:
+55.0/+2000.0
Vibration Resistance Amplitude:
35.0 gravitational units
Shock Resistance Rating In Gravitational Units:
1000.0
Operating Tempurature Range:
-0.0/+70.0 degrees celsius
Average Life Measurement:
Not rated
Basic Shape Style:
Rectangular or square
Identification Designator:
K1100a-04713
Inclosure Type:
Encased
Installation Design:
Module
Circuit Construction Type:
Any acceptable
Frequency Per Channel:
15.750 megahertz operating channel
Signal Voltage Rating Per Channel:
5.000 volts input
Shock Pulse Duration Time:
0.35 milliseconds
Connection Type And Location:
Solder lug bottom
Connection Contact Type And Quantity:
4 solder lug external
External Dc Operating Voltage In Volts:
5.0 single voltage
Precious Material And Location:
Pin surfaces gold
5

NSN 5955-01-110-9923

Crystal Controlled Oscillator - Page 2 of 2

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A32200

