# NSN 5955-01-112-6188

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-112-6188

Overall Length:

0.530 inches

**Terminal Length:** 

0.500 inches

## **Overall Width:**

0.435 inches

#### Body Width:

0.402 inches

#### Body Thickness:

0.150 inches

#### **Overall Thickness:**

0.183 inches

**Terminal Diameter:** 

Between 0.016 inches and 0.019 inches

### Mode Of Oscillation:

Fundamental

#### **Circuit Resonance:**

Antiresonance

### Load Capacitance In Picofarads:

29.5

### Shunt Capacitance In Picofarads:

Between 3.7 and 7.0

### **Specified Frequency:**

6.144 megahertz

### Holder Cover Material:

Metal

### **Operating Tempurature Range:**

-55.0/+105.0 degrees celsius

### Center To Center Distance Between Terminals:

0.184 mils and 0.200 centimeters

#### **Drive Level Rating:**

5.0 milliwatts

### Frequency Tolerance For Operating Tempurature In Percent:

-0.005/+0.005

### **Equivalent Resistance Value In Ohms:**

50.0

## Style Designator:

Oval body, wire leads

## Test Data Document:

81349-mil-c-3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Specification Data:

81349-mil-c-3098/42 government specification

# NSN 5955-01-112-6188

Quartz Crystal Unit - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A059a0

