## NSN 5955-01-113-3281

Crystal Controlled Oscillator - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5955-01-113-3281



**Overall Length:** 0.820 inches **Overall Height:** 0.425 inches **Overall Width:** 0.520 inches **Environmental Protection:** Shock resistant and vibration **Vibration Resistance Range In Hertz:** +55.0/+2000.0 **Vibration Resistance Amplitude:** 35.0 gravitational units **Shock Resistance Rating In Gravitational Units:** 100.0 **Operating Tempurature Range:** -0.0/+70.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Identification Designator:** K1114a-04713 **Inclosure Type:** Encased **Installation Design:** Module **Circuit Construction Type:** Any acceptable Frequency Per Channel: 10.000 megahertz operating channel Signal Voltage Rating Per Channel: 5.000 volts input **Shock Pulse Duration Time:** 0.1 milliseconds **Connection Type And Location:** Solder lug bottom **Connection Contact Type And Quantity:** 4 solder lug external **External Dc Operating Voltage In Volts:** 5.0 single voltage **Precious Material And Location:** 

Pin surfaces gold

## NSN 5955-01-113-3281

Crystal Controlled Oscillator - Page 2 of 2



Precious Mat	eria	l:
--------------	------	----

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A32200