Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-117-9899

## **Overall Length:** 0.830 inches **Overall Diameter:** 0.565 inches **Environmental Protection:** Moisture proof and vibration **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -62.0/+150.0 degrees celsius Average Life Measurement: Not rated **Basic Shape Style:** Cylindrical **Inclosure Type:** Hermetically sealed **Operating Control Method:** Automatic Installation Design: Module **Control Type:** Remote **Circuit Construction Type:** Solid state **Frequency Per Channel:** 6.0 megahertz operating channel **Connection Type And Location:** Err-060 glad hand quick disconnect **Connection Contact Type And Quantity:** 8 liters of liquid nitrogen drain **External Dc Operating Voltage In Volts:** 4.75 single voltage and 5.25 single voltage **Special Features:** length included 0.480 in. Pin length **Test Data Document:** 81349-mil-o-55310 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Data:** 81349-mil-o-55310/10 government specification Shelf Life:

N/a

Crystal Controlled Oscillator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A32200