## NSN 5955-01-121-0304

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-121-0304 **Overall Length:** 0.820 inches **Overall Height:** 0.425 inches **Overall Width:** 0.520 inches **Environmental Protection:** Shock resistant and vibration **Vibration Resistance Range In Hertz:** +55.0/+2000.0 **Vibration Resistance Amplitude:** 35.0 gravitational units **Shock Resistance Rating In Gravitational Units:** 1000.0 **Operating Tempurature Range:** +0.0/+70.0 degrees celsius **Storage Tempurature Range:** -55.0/+125.0 degrees celsius **Average Life Measurement:** Not rated **End Application:** Jetds type no. Cp-1498/g, computers **Basic Shape Style:** Rectangular or square **Identification Designator:** K1100a28.500mhz-04713 **Inclosure Type:** Hermetically sealed Installation Design: Module **Circuit Construction Type:** Solid state Frequency Per Channel: 28.5 megahertz operating channel **Shock Pulse Duration Time:** 0.35 milliseconds **Connection Type And Location:** Printed circuit bottom **Connection Contact Type And Quantity:** 14 printed circuit external **External Dc Operating Voltage In Volts:** 

5.0 single voltage

## NSN 5955-01-121-0304

Crystal Controlled Oscillator - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A32200