Crystal Controlled Oscillator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5955-01-122-3457

| | Overall Length: |
|----|---|
| | .800 inches |
| | Overall Height: |
| | .555 inches |
| | Overall Width: |
| | .500 inches |
| | Operating Tempurature Range: |
| -{ | 55.0/+125.0 degrees celsius |
| | storage Tempurature Range: |
| -6 | 62.0/+125.0 degrees celsius |
| A | verage Life Measurement: |
| Ν | lot rated |
| B | Basic Shape Style: |
| R | Rectangular or square |
| lo | dentification Designator: |
| 6 | 35a715-97942 |
| Ir | nclosure Type: |
| F | lermetically sealed |
| C | Operating Control Method: |
| A | utomatic |
| Ir | nstallation Design: |
| N | lodule |
| C | Control Type: |
| R | Remote |
| C | Circuit Construction Type: |
| | Solid state |
| | requency Per Channel: |
| 1 | 0.3448 megahertz operating channel |
| | Connection Type And Location: |
| P | Pin bottom |
| C | Connection Contact Type And Quantity: |
| | pin external |
| E | External Dc Operating Voltage In Volts: |
| | .0 single voltage |
| S | Shelf Life: |
| | I/a |
| U | Init Of Measure: |
| | |
| D | Demilitarization: |
| Ν | lo |
| F | iig: |
| Α | 32200 |