Noncrystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-122-4945

| Overall Length |
|---|
| Overall Length: 1.170 inches |
| |
| Overall Diameter: |
| 1.740 inches |
| Environmental Protection: |
| Vibration and shock resistant |
| Vibration Resistance Range In Hertz: |
| +10.0/+55.0 |
| Vibration Resistance Amplitude: |
| 0.02 inches total excursion |
| Shock Resistance Rating In Gravitational Units: |
| Not rated |
| Operating Tempurature Range: |
| +0.0/+60.0 degrees celsius |
| Storage Tempurature Range: |
| -40.0/+75.0 degrees celsius |
| Average Life Measurement: |
| Not rated |
| End Application: |
| 6625-00-367-9335, analyzer, spectrum |
| Basic Shape Style: |
| Cylindrical |
| Maximum Operating Altitude Rating: |
| Not rated |
| Inclosure Type: |
| Hermetically sealed |
| Installation Design: |
| Module |
| Circuit Construction Type: |
| Solid state |
| |
| Frequency Per Channel: |
| Frequency Per Channel: 2.0 gigabertz, output channel and 4.1 gigabertz, output channel |
| 2.0 gigahertz output channel and 4.1 gigahertz output channel |
| 2.0 gigahertz output channel and 4.1 gigahertz output channel Attenuation In Decibels: |
| 2.0 gigahertz output channel and 4.1 gigahertz output channelAttenuation In Decibels:1.5 |
| 2.0 gigahertz output channel and 4.1 gigahertz output channel Attenuation In Decibels: 1.5 Average Power Rating Per Channel: |
| 2.0 gigahertz output channel and 4.1 gigahertz output channel Attenuation In Decibels: 1.5 Average Power Rating Per Channel: 15.0 milliwatts output |
| 2.0 gigahertz output channel and 4.1 gigahertz output channel Attenuation In Decibels: 1.5 Average Power Rating Per Channel: 15.0 milliwatts output Signal Voltage Rating Per Channel: |
| 2.0 gigahertz output channel and 4.1 gigahertz output channel Attenuation In Decibels: 1.5 Average Power Rating Per Channel: 15.0 milliwatts output Signal Voltage Rating Per Channel: 15.000 volts output |
| 2.0 gigahertz output channel and 4.1 gigahertz output channel Attenuation In Decibels: 1.5 Average Power Rating Per Channel: 15.0 milliwatts output Signal Voltage Rating Per Channel: 15.000 volts output Overall Gain: |
| 2.0 gigahertz output channel and 4.1 gigahertz output channel Attenuation In Decibels: 1.5 Average Power Rating Per Channel: 15.0 milliwatts output Signal Voltage Rating Per Channel: 15.000 volts output Overall Gain: 1.5 decibels |
| 2.0 gigahertz output channel and 4.1 gigahertz output channel Attenuation In Decibels: 1.5 Average Power Rating Per Channel: 15.0 milliwatts output Signal Voltage Rating Per Channel: 15.000 volts output Overall Gain: |



Maximum Continuous Operating Time In Hours: Not rated Connection Type And Location: Printed circuit bottom **Connection Contact Type And Quantity:** 14 printed circuit external External Dc Operating Voltage In Volts: 15.0 single voltage Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A32200