## NSN 5955-01-123-0651

**Overall Length:** 

Crystal Controlled Oscillator - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5955-01-123-0651



0.600 inches **Overall Height:** 0.400 inches **Overall Width:** 0.500 inches **Environmental Protection:** Vibration and shock resistant **Vibration Resistance Range In Hertz:** +10.0/+55.0 **Vibration Resistance Amplitude:** 0.06 inches total excursion **Shock Resistance Rating In Gravitational Units:** 30.0 **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Storage Tempurature Range:** -55.0/+125.0 degrees celsius **Average Life Measurement:** Not rated **End Application:** F-16 aircraft **Basic Shape Style:** Rectangular or square **Maximum Operating Altitude Rating:** 100000.000 feet **Inclosure Type:** Hermetically sealed Installation Design: Module **Circuit Construction Type:** Solid state Frequency Per Channel: 16.0 megahertz output channel **Attenuation In Decibels:** Not rated **Average Power Rating Per Channel:** Not rated Signal Voltage Rating Per Channel: Not rated **Overall Gain:** 80.0 milliamperes

## NSN 5955-01-123-0651

Crystal Controlled Oscillator - Page 2 of 2



Impedance Rating Per Channel:
Not rated
<b>Maximum Continuous Operating Time In Hours:</b>
Not rated
Shock Pulse Duration Time:
11.0 milliseconds
Connection Type And Location:
Printed circuit bottom
Connection Contact Type And Quantity:
14 printed circuit external
External Dc Operating Voltage In Volts:
5.0 single voltage
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

**Fiig:** A32200