## NSN 5955-01-123-8736

Noncrystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-123-8736 **Overall Length:** 0.800 inches **Overall Height:** 0.375 inches **Overall Width:** 0.500 inches **Vibration Resistance Range In Hertz:** -10.0/+2000.0 **Vibration Resistance Amplitude:** 20.0 gravitational units **Shock Resistance Rating In Gravitational Units:** 100.0 **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Average Life Rating:** 168.0 **Average Life Measurement:** Hours **Average Life Rating In Hours:** 168.0 **Basic Shape Style:** Rectangular or square **Identification Designator:** C0-238b-2c-20mhz-27802 **Maximum Operating Altitude Rating:** Not rated Inclosure Type: Hermetically sealed Installation Design: Module **Circuit Construction Type:** Solid state Frequency Per Channel: 20.0 megahertz input channel Frequency Adjustment Type: Continuous **Attenuation In Decibels:** Not rated **Average Power Rating Per Channel:** Not rated Signal Voltage Rating Per Channel:

Not rated

## NSN 5955-01-123-8736

Noncrystal Controlled Oscillator - Page 2 of 2



Overall Gain:
Not rated
Impedance Rating Per Channel:
Not rated
Maximum Continuous Operating Time In Hours:
7.0
Shock Pulse Duration Time:
6.0 microseconds
Connection Type And Location:
Wire lead terminals bottom
Connection Contact Type And Quantity:
8 wire lead terminals external
External Dc Operating Voltage In Volts:
5.0 single voltage
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A32200