NSN 5955-01-124-5574

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-124-5574

| g |
|---|
| Overall Length: |
| Between 0.220 inches and 0.265 inches |
| Terminal Length: |
| 0.500 inches |
| Diameter: |
| Between 0.310 inches and 0.330 inches |
| Overall Diameter: |
| Between 0.350 inches and 0.380 inches |
| Terminal Diameter: |
| Between 0.016 inches and 0.019 inches |
| Mode Of Oscillation: |
| Fifth overtone |
| Circuit Resonance: |
| Series resonance |
| Shunt Capacitance In Picofarads: |
| Between 2.8 and 4.8 |
| Specified Frequency: |
| 116.444 megahertz |
| Holder Cover Material: |
| Metal or glass |
| Operating Tempurature Range: |
| -55.0/+85.0 degrees celsius |
| Center To Center Distance Between Terminals: |
| 0.190 mils and 0.210 centimeters |
| Drive Level Rating: |
| 0.4 milliwatts |
| Frequency Tolerance For Operating Tempurature In Percent: |
| -0.0025/+0.0025 |
| Equivalent Resistance Value In Ohms: |
| 55.0 |
| Precious Material And Location: |
| Terminals gold |
| Precious Material: |
| Gold |
| Style Designator: |
| Hat type, 3 wire leads |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

Demilitarization:

Yes - demil/mli

NSN 5955-01-124-5574

Quartz Crystal Unit - Page 2 of 2



Fiig:

A059a0