NSN 5955-01-125-2220

Pulse Delay Oscillator - Page 1 of 2

Between 5.215 inches and 5.235 inches

Between 0.572 inches and 0.592 inches

Overall Length:

Overall Height:



View Online at https://aerobasegroup.com/nsn/5955-01-125-2220

Overall Width:
Between 2.840 inches and 2.860 inches
Vibration Resistance Range In Hertz:
Not rated
Shock Resistance Rating In Gravitational Units:
Not rated
Operating Tempurature Range:
-62.0/+85.0 degrees celsius
Average Life Measurement:
Not rated
End Application:
Irs-alr 46/69
Basic Shape Style:
Rectangular or square
Identification Designator:
40145-17-97384
Maximum Operating Altitude Rating:
15000.000 feet
Inclosure Type:
Open
Installation Design:
Mechanical
Circuit Construction Type:
Solid state
Frequency Per Channel:
1080.0 megahertz output channel err-100
Attenuation In Decibels:
Not rated
Average Power Rating Per Channel:
Not rated
Signal Voltage Rating Per Channel:
80.500 volts input preset
Overall Gain:
Not rated
Impedance Rating Per Channel:
Not rated
Pulse Peak Amplitude Per Channel:
Not rated

NSN 5955-01-125-2220

Pulse Delay Oscillator - Page 2 of 2



Signal Data Type Per Channel:
Output channel pulse delay
Output Wave Shape:
Pulse, sweep
Maximum Continuous Operating Time In Hours:
Not rated
External Ac Operating Voltage In Volts:
5.0 1st voltage
Reference Number Differentiating Characteristics:
As differentiated by the source control dwg.No.58744-90017
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A32200