# NSN 5955-01-125-2220

Pulse Delay Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-125-2220

## **Overall Length:** Between 5.215 inches and 5.235 inches **Overall Height:** Between 0.572 inches and 0.592 inches Overall Width: Between 2.840 inches and 2.860 inches **Vibration Resistance Range In Hertz:** Not rated **Shock Resistance Rating In Gravitational Units:** Not rated **Operating Tempurature Range:** -62.0/+85.0 degrees celsius **Average Life Measurement:** Not rated **End Application:** Irs-alr 46/69 **Basic Shape Style:** Rectangular or square Identification Designator: 40145-17-97384 Maximum Operating Altitude Rating: 15000.000 feet Inclosure Type: Open Installation Design: Mechanical **Circuit Construction Type:** Solid state **Frequency Per Channel:** 1080.0 megahertz output channel err-100 Attenuation In Decibels: Not rated **Average Power Rating Per Channel:** Not rated Signal Voltage Rating Per Channel: 80.500 volts input preset **Overall Gain:** Not rated **Impedance Rating Per Channel:** Not rated **Pulse Peak Amplitude Per Channel:** Not rated

## NSN 5955-01-125-2220

Pulse Delay Oscillator - Page 2 of 2



## Signal Data Type Per Channel:

Output channel pulse delay

### **Output Wave Shape:**

Pulse, sweep

## Maximum Continuous Operating Time In Hours:

Not rated

## External Ac Operating Voltage In Volts:

5.0 1st voltage

## **Reference Number Differentiating Characteristics:**

As differentiated by the source control dwg.No.58744-90017

Shelf Life:

N/a

### Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

#### Fiig:

A32200