Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-125-2530

Overall Length:1.500 inchesOverall Height:0.910 inchesOverall Width:1.500 inchesEnvironmental Protection:Shock resistant and vibrationVibration Resistance Range In Hertz:+55.0/+500.0Operating Tempurature Range:+0.0/+70.0 degrees celsiusStorage Tempurature Range:-55.0/+125.0 degrees celsiusAverage Life Measurement:Not rated
Overall Height:0.910 inchesOverall Width:1.500 inchesEnvironmental Protection:Shock resistant and vibrationVibration Resistance Range In Hertz:+55.0/+500.0Operating Tempurature Range:+0.0/+70.0 degrees celsiusStorage Tempurature Range:-55.0/+125.0 degrees celsiusAverage Life Measurement:
0.910 inches Overall Width: 1.500 inches Environmental Protection: Shock resistant and vibration Vibration Resistance Range In Hertz: +55.0/+500.0 Operating Tempurature Range: +0.0/+70.0 degrees celsius Storage Tempurature Range: -55.0/+125.0 degrees celsius Average Life Measurement:
Overall Width:1.500 inchesEnvironmental Protection:Shock resistant and vibrationVibration Resistance Range In Hertz:+55.0/+500.0Operating Tempurature Range:+0.0/+70.0 degrees celsiusStorage Tempurature Range:-55.0/+125.0 degrees celsiusAverage Life Measurement:
 1.500 inches Environmental Protection: Shock resistant and vibration Vibration Resistance Range In Hertz: +55.0/+500.0 Operating Tempurature Range: +0.0/+70.0 degrees celsius Storage Tempurature Range: -55.0/+125.0 degrees celsius Average Life Measurement:
Environmental Protection: Shock resistant and vibration Vibration Resistance Range In Hertz: +55.0/+500.0 Operating Tempurature Range: +0.0/+70.0 degrees celsius Storage Tempurature Range: -55.0/+125.0 degrees celsius Average Life Measurement:
Shock resistant and vibration Vibration Resistance Range In Hertz: +55.0/+500.0 Operating Tempurature Range: +0.0/+70.0 degrees celsius Storage Tempurature Range: -55.0/+125.0 degrees celsius Average Life Measurement:
Vibration Resistance Range In Hertz: +55.0/+500.0 Operating Tempurature Range: +0.0/+70.0 degrees celsius Storage Tempurature Range: -55.0/+125.0 degrees celsius Average Life Measurement:
+55.0/+500.0 Operating Tempurature Range: +0.0/+70.0 degrees celsius Storage Tempurature Range: -55.0/+125.0 degrees celsius Average Life Measurement:
Operating Tempurature Range: +0.0/+70.0 degrees celsius Storage Tempurature Range: -55.0/+125.0 degrees celsius Average Life Measurement:
+0.0/+70.0 degrees celsius Storage Tempurature Range: -55.0/+125.0 degrees celsius Average Life Measurement:
Storage Tempurature Range: -55.0/+125.0 degrees celsius Average Life Measurement:
-55.0/+125.0 degrees celsius Average Life Measurement:
Average Life Measurement:
-
Not rated
End Application:
Data acquisition set, jetds type no. An/gsq-20 (v) 1
Basic Shape Style:
Rectangular or square
Identification Designator:
119-0957-00-80009
Maximum Operating Altitude Rating:
100000.000 feet
Inclosure Type:
Hermetically sealed
Installation Design:
Module
Circuit Construction Type:
Solid state
Frequency Per Channel:
200.0 megahertz output channel
Connection Type And Location:
Printed circuit bottom
Connection Contact Type And Quantity:
5 printed circuit external
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5955-01-125-2530

Crystal Controlled Oscillator - Page 2 of 2

Fiig: A32200

