

NSN 5955-01-125-9515 Crystal Controlled Oscillator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5955-01-125-9515 **Overall Length:** 0.875 inches **Overall Height:** 0.425 inches **Overall Width:** 0.500 inches **Environmental Protection:** Shock resistant and vibration **Vibration Resistance Range In Hertz:** +10.0/+50.0 **Vibration Resistance Amplitude:** 0.06 inches total excursion **Shock Resistance Rating In Gravitational Units:** 1000.0 **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Identification Designator:** P164-001-10-95542 **Inclosure Type:** Hermetically sealed Installation Design: Module **Circuit Construction Type:** Solid state

Frequency Per Channel:

1.152 megahertz output channel

Overall Gain:

60.0 milliamperes

Shock Pulse Duration Time:

1.0 milliseconds

Connection Type And Location:

Printed circuit bottom

Connection Contact Type And Quantity:

14 printed circuit external

External Dc Operating Voltage In Volts:

5.0 single voltage

Shelf Life:

N/a

NSN 5955-01-125-9515

Crystal Controlled Oscillator - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200