

NSN 5955-01-126-7419 Noncrystal Controlled Oscillator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5955-01-126-7419 **Overall Length:** 4.300 inches **Overall Height:** 3.500 inches **Overall Width:** 4.000 inches Vibration Resistance Range In Hertz: +4.0/+33.0 **Vibration Resistance Amplitude:** 0.100 inches total excursion **Shock Resistance Rating In Gravitational Units:** 50.0 **Operating Tempurature Range:** -28.0/+85.0 degrees celsius **Average Life Rating:** 10000.0 **Average Life Measurement:** Hours **Average Life Rating In Hours:** 10000.0 **Basic Shape Style:** Rectangular or square **Identification Designator:** 2622969-28527 **Maximum Operating Altitude Rating:** Not rated

Operating Control Method:

Automatic

Installation Design:

Rack

Circuit Construction Type:

Solid state

Attenuation In Decibels:

3.0

Impedance Rating Per Channel:

10.000 kilohms operating channel

Maximum Continuous Operating Time In Hours:

50000.0

Shock Pulse Duration Time:

11.0 milliseconds

Connection Type And Location:

Integral cable w/coaxial plug left side and integral cable w/coaxial plug right side and integral cable w/power plug bottom

NSN 5955-01-126-7419

Noncrystal Controlled Oscillator - Page 2 of 2



Connection Contact Type And Quantity:

5 integral cable w/coaxial plug external and 1 integral cable w/power plug external

External Dc Operating Voltage In Volts:

28.0 3rd voltage err-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200