NSN 5955-01-142-3409

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-142-3409 **Overall Length:** 0.420 inches **Overall Diameter:** 0.500 inches **Environmental Protection:** Shock resistant and vibration **Operating Tempurature Range:** -54.0/+71.0 degrees celsius **Storage Tempurature Range:** -54.0/+125.0 degrees celsius **Average Life Measurement:** Not rated **End Application:** 5865-01-109-1692, exciter **Basic Shape Style:** Cylindrical **Identification Designator:** Mto-8060-24539 **Inclosure Type:** Encased **Operating Control Method:** Automatic Installation Design: Module **Control Type:** Remote **Circuit Construction Type:** Solid state Frequency Per Channel: 600.0 megahertz output channel and 900.0 megahertz output channel **Attenuation In Decibels:** 10.0 **Overall Gain:** 50.0 milliamperes Impedance Rating Per Channel: 50.000 ohms operating channel **Connection Type And Location:** Printed circuit bottom

Connection Contact Type And Quantity:

3 printed circuit external

External Dc Operating Voltage In Volts:

15.0 single voltage

NSN 5955-01-142-3409

Crystal Controlled Oscillator - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A32200