NSN 5955-01-145-0449

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-145-0449

Overall Length:

Between 0.220 inches and 0.260 inches

Terminal Length:

0.620 inches

Diameter:

Between 0.305 inches and 0.335 inches

Overall Diameter:

0.420 inches

Terminal Diameter:

Between 0.048 inches and 0.052 inches

Mode Of Oscillation:

Fundamental

Circuit Resonance:

Antiresonance

Load Capacitance In Picofarads:

Between 32.5 and 33.5

Shunt Capacitance In Picofarads:

7.0

Specified Frequency:

4.096 megahertz

Frequency Tolerance At Reference Tempurature In Percent:

-0.007/+0.007

Frequency Stability In Percent:

-0.001/+0.001

Controlled Reference Temp:

40.0 degrees celsius

Operable Tempurature Range:

+0.0/+80.0 degrees celsius

Holder Cover Material:

Metal

Operating Tempurature Range:

-55.0/+115.0 degrees celsius

End Application:

6625-00-229-1049

Center To Center Distance Between Terminals:

0.190 mils and 0.210 centimeters

Drive Level Rating:

Between 0.7 milliwatts and 1.0 milliwatts

Frequency Tolerance For Operating Tempurature In Percent:

-0.002/+0.002 and -0.005/+0.005

Equivalent Resistance Value In Ohms:

150.0

NSN 5955-01-145-0449

Quartz Crystal Unit - Page 2 of 2



•	_			
Style	1)6	SIU	na	t∩r∙
Otylo		JIG	ııu	w.

Hat type, 3 wire leads

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A059a0