

NSN 5955-01-146-2906 Crystal Controlled Oscillator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5955-01-146-2906 **Overall Length:** 0.812 inches **Overall Height:** 0.540 inches **Overall Width:** 0.500 inches **Environmental Protection:** Shock resistant and vibration **Vibration Resistance Range In Hertz:** Not rated **Shock Resistance Rating In Gravitational Units:** Not rated **Operating Tempurature Range:** -0.0/+70.0 degrees celsius **Average Life Measurement:** Not rated **End Application:** 4920-01-049-0223, singer automatic im **Basic Shape Style:** Rectangular or square **Identification Designator:** 1813-01-432-8480 **Maximum Operating Altitude Rating:** Not rated **Inclosure Type:** Encased **Installation Design:** Module

Circuit Construction Type:

Solid state

Frequency Per Channel:

19.6608 megahertz output channel

Attenuation In Decibels:

Not rated

Average Power Rating Per Channel:

Signal Voltage Rating Per Channel:

5.000 volts input

Overall Gain:

45.0 milliamperes

Impedance Rating Per Channel:

Not rated

NSN 5955-01-146-2906

Crystal Controlled Oscillator - Page 2 of 2



| Maximum Continuous Operating Time In Hours: |
|---|
| Not rated |
| Connection Type And Location: |
| Printed circuit bottom |
| Connection Contact Type And Quantity: |
| 4 printed circuit external |
| External Dc Operating Voltage In Volts: |
| 5.0 single voltage |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

Yes - demil/mli

Fiig: A32200