Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-146-6745

Overall Length:
2.150 inches
Overall Height:
0.718 inches
Overall Width:
1.522 inches
Environmental Protection:
Shock resistant and vibration
Vibration Resistance Range In Hertz:
Not rated
Shock Resistance Rating In Gravitational Units:
Not rated
Operating Tempurature Range:
-29.0/+85.0 degrees celsius
Storage Tempurature Range:
-57.0/+85.0 degrees celsius
Average Life Measurement:
Not rated
Basic Shape Style:
Rectangular or square
Identification Designator:
Sm-a-838150-3-18.432mhz-80063
Maximum Operating Altitude Rating:
Not rated
Inclosure Type:
Hermetically sealed
Operating Control Method:
Manual
Installation Design:
Module
Control Type:
Local
Circuit Construction Type:
Solid state
Frequency Per Channel:
18.432 megahertz output channel
Attenuation In Decibels:
Not rated
Average Power Rating Per Channel:
0.45 watts input
Signal Voltage Rating Per Channel:
5.000 volts input and 15.000 volts input

## NSN 5955-01-146-6745

Crystal Controlled Oscillator - Page 2 of 2



**Overall Gain:** 40.0 milliamperes Impedance Rating Per Channel: 5.000 kilohms input channel Maximum Continuous Operating Time In Hours: Not rated **Connection Type And Location:** Printed circuit bottom **Connection Contact Type And Quantity:** 6 printed circuit external **External Dc Operating Voltage In Volts:** 15.0 single voltage Shelf Life: N/a Unit Of Measure: ---Demilitarization: Yes - demil/mli Fiig: A32200