## NSN 5955-01-146-6746

Crystal Controlled Oscillator - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5955-01-146-6746



**Overall Length:** 2.150 inches **Overall Height:** 0.718 inches **Overall Width:** 1.522 inches **Environmental Protection:** Shock resistant and vibration **Vibration Resistance Range In Hertz:** Not rated **Shock Resistance Rating In Gravitational Units:** Not rated **Operating Tempurature Range:** -29.0/+85.0 degrees celsius **Storage Tempurature Range:** -57.0/+85.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Identification Designator:** Sm-a-838150-1-12.288mhz-80063 **Maximum Operating Altitude Rating:** Not rated **Inclosure Type:** Hermetically sealed **Operating Control Method:** Manual Installation Design: Module **Control Type: Circuit Construction Type:** Solid state Frequency Per Channel: 12.288 megahertz output channel **Attenuation In Decibels:** Not rated **Average Power Rating Per Channel:** 0.45 watts input Signal Voltage Rating Per Channel: 5.000 volts input and 15.000 volts input

## NSN 5955-01-146-6746

Crystal Controlled Oscillator - Page 2 of 2



Overall G	aır	۱:
-----------	-----	----

40.0 milliamperes

Impedance Rating Per Channel:

5.000 kilohms input channel

**Maximum Continuous Operating Time In Hours:** 

Not rated

**Connection Type And Location:** 

Printed circuit bottom

**Connection Contact Type And Quantity:** 

6 printed circuit external

**External Dc Operating Voltage In Volts:** 

15.0 single voltage

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200