NSN 5955-01-149-2560

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-149-2560						
Overall Length:						
0.887 inches						
Overall Height:						
0.400 inches						
Overall Width:						
0.540 inches						
Environmental Protection:						
Shock resistant and vibration						
Vibration Resistance Range In Hertz:						
+1.0/+10.0						
Operating Tempurature Range:						
-55.0/+125.0 degrees celsius						
Storage Tempurature Range:						
-62.0/+125.0 degrees celsius						
Average Life Measurement:						
Not rated						
End Application:						
Jetds no. An/tpb-1d, radar bomb directing set						
Basic Shape Style:						
Rectangular or square						
Identification Designator:						
M55310/16-b24a2.4576mhz-81349						
Inclosure Type:						
Hermetically sealed						
Installation Design:						
Module						
Circuit Construction Type:						
Solid state						
Frequency Per Channel:						
2.4576 megahertz output channel						
Signal Voltage Rating Per Channel:						
2.400 volts output and 0.500 volts output						
Connection Type And Location:						
Printed circuit bottom						
Connection Contact Type And Quantity:						
14 printed circuit external						
External Dc Operating Voltage In Volts:						
5.0 single voltage						
Test Data Document:						
81349-mil-o-55310 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification						
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain						

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

NSN 5955-01-149-2560

Crystal Controlled Oscillator - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A32200