Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-150-1757

Overall Length:	
0.887 inches	
Overall Height:	
0.400 inches	
Overall Width:	
0.540 inches	
Environmental Protection:	
Shock resistant and vibration	
Operating Tempurature Range:	
-55.0/+125.0 degrees celsius	
Storage Tempurature Range:	
-62.0/+125.0 degrees celsius	
Average Life Measurement:	
Not rated	
End Application:	
5865-01-109-1702, control, amplifier	
Basic Shape Style:	
Rectangular or square	
Identification Designator:	
M55310/14-b06a4.000000mhz-81349	
Inclosure Type:	
Hermetically sealed	
Installation Design:	
Module	
Circuit Construction Type:	
Solid state	
Frequency Per Channel:	
4.0 megahertz output channel	
Connection Type And Location:	
Err-060 glad hand quick disconnect	
Connection Contact Type And Quantity:	
14 liters of liquid nitrogen drain	
External Dc Operating Voltage In Volts:	
4.5 single voltage and 5.5 single voltage	
Test Data Document:	
81349-mil-o-55310 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification	
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Specification Data:	
81349-mil-o-55310/14 government specification	
Shelf Life:	
N/a	

Unit Of Measure:

Crystal Controlled Oscillator - Page 2 of 2

AeroBase Group

Demilitarization:

No

Fiig:

A32200