

NSN 5955-01-150-1865 Crystal Controlled Oscillator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5955-01-150-1865 **Overall Length:** 0.800 inches **Overall Height:** 0.400 inches **Overall Width:** 0.540 inches **Environmental Protection:** Shock resistant and vibration **Vibration Resistance Range In Hertz:** +1.0/+10.0 **Vibration Resistance Amplitude:** 20.0 gravitational units **Shock Resistance Rating In Gravitational Units:** 100.0 **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Identification Designator:** C8877-8-20mhz-81755 **Maximum Operating Altitude Rating:** 100000.0 feet **Inclosure Type:** Hermetically sealed Installation Design: Module **Circuit Construction Type:** 

Solid state

Frequency Per Channel:

20.0 megahertz output channel

**Attenuation In Decibels:** 

2.0

**Signal Voltage Rating Per Channel:** 

0.400 volts output and 2.400 volts output

**Overall Gain:** 

80.0 milliamperes

**Shock Pulse Duration Time:** 

6.0 milliseconds

**Connection Type And Location:** 

Printed circuit bottom

## NSN 5955-01-150-1865

Crystal Controlled Oscillator - Page 2 of 2



Connection Contact	ct Type	And	Quantity	<b>/</b> :
--------------------	---------	-----	----------	------------

14 printed circuit external

**External Dc Operating Voltage In Volts:** 

5.0 single voltage

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A32200