Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-150-4626

Overall Length: 0.887 inches **Overall Height:** 0.400 inches **Overall Width:** 0.540 inches **Environmental Protection:** Shock resistant and vibration **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -62.0/+125.0 degrees celsius Average Life Measurement: Not rated **Basic Shape Style:** Rectangular or square **Identification Designator:** M55310/14-b08a12.000000mhz-81349 Inclosure Type: Hermetically sealed Installation Design: Module **Circuit Construction Type:** Solid state **Frequency Per Channel:** 12.0 megahertz operating channel **Connection Type And Location:** Err-060 glad hand quick disconnect **Connection Contact Type And Quantity:** 14 liters of liquid nitrogen drain **External Dc Operating Voltage In Volts:** 4.5 single voltage and 5.5 single voltage **Test Data Document:** 81349-mil-o-55310 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Data:** 81349-mil-o-55310/14 government specification Shelf Life: N/a Unit Of Measure: **Demilitarization:** No

NSN 5955-01-150-4626

Crystal Controlled Oscillator - Page 2 of 2

Fiig: A32200

