

View Online at <https://aerobasegroup.com/nsn/5955-01-150-8194>

Overall Length:

0.800 inches

Overall Height:

0.555 inches

Overall Width:

0.500 inches

Environmental Protection:

Shock resistant and vibration

Vibration Resistance Range In Hertz:

+1.0/+10.0

Vibration Resistance Amplitude:

20.0 gravitational units

Shock Resistance Rating In Gravitational Units:

100.0

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-55.0/+125.0 degrees celsius

Average Life Measurement:

Not rated

Basic Shape Style:

Rectangular or square

Identification Designator:

Co-238a-2s-2@10mhz-27802

Maximum Operating Altitude Rating:

100000.0 feet

Inclosure Type:

Hermetically sealed

Installation Design:

Module

Circuit Construction Type:

Solid state

Frequency Per Channel:

10.0 megahertz output channel

Attenuation In Decibels:

Not rated

Average Power Rating Per Channel:

Not rated

Signal Voltage Rating Per Channel:

0.400 volts output and 2.400 volts output

Overall Gain:

20.0 milliamperes

Impedance Rating Per Channel:

Not rated

Maximum Continuous Operating Time In Hours:

Not rated

Shock Pulse Duration Time:

6.0 milliseconds

Connection Type And Location:

Printed circuit bottom

Connection Contact Type And Quantity:

14 printed circuit external

External Dc Operating Voltage In Volts:

5.0 single voltage

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200