NSN 5955-01-150-8345

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-150-8345						
Overall Length:						
0.887 inches						
Overall Height:						
0.400 inches						
Overall Width:						
0.540 inches						
Environmental Protection:						
Shock resistant and vibration						
Operating Tempurature Range:						
-55.0/+125.0 degrees celsius						
Storage Tempurature Range:						
-62.0/+125.0 degrees celsius						
Average Life Measurement:						
Not rated						
Basic Shape Style:						
Rectangular or square						
Identification Designator:						
M55310/16-b21a-2.457600mhz-81349						
Inclosure Type:						
Hermetically sealed						
Operating Control Method:						
Automatic						
Installation Design:						
Module						
Control Type:						
Remote						
Circuit Construction Type:						
Solid state						
Frequency Per Channel:						
2.4576 megahertz operating channel						
Connection Type And Location:						
Pin bottom						
Connection Contact Type And Quantity:						
14 pin external						
External Dc Operating Voltage In Volts:						
4.5 single voltage and 5.5 single voltage						
Test Data Document:						
81349-mil-prf-55310 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification						
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain						
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).						
Specification Data:						

Shelf Life:

81349-mil-c-3098/16 government specification

N/a

NSN 5955-01-150-8345

Crystal Controlled Oscillator - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200

Mil-std (military Standard):

Mil-prf-55310 spec.