NSN 5955-01-150-8830

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-150-8830
Overall Length:
0.887 inches
Overall Height:
0.400 inches
Overall Width:
0.540 inches
Environmental Protection:
Shock resistant and vibration
Vibration Resistance Range In Hertz:
+1.0/+6.0
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-62.0/+125.0 degrees celsius
Average Life Measurement:
Not rated
Basic Shape Style:
Rectangular or square
Identification Designator:
M55310/16-b41a20mhz-81349
Inclosure Type:
Hermetically sealed
Installation Design:
Module
Circuit Construction Type:
Solid state
Frequency Per Channel:
20.0 megahertz output channel
Signal Voltage Rating Per Channel:
0.500 volts output and 2.400 volts output
Overall Gain:
65.0 milliamperes
Connection Type And Location:
Printed circuit bottom
Connection Contact Type And Quantity:
14 printed circuit external
External Dc Operating Voltage In Volts:
5.0 single voltage
Test Data Document:
81349-mil-o-55310 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

N/a

Shelf Life:

NSN 5955-01-150-8830

Crystal Controlled Oscillator - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200