## NSN 5955-01-151-1310

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-151-1310

Overall Length:
0.800 inches
Overall Height:
0.420 inches
Overall Width:
0.500 inches
Environmental Protection:
Shock resistant and vibration
Vibration Resistance Range In Hertz:
+10.0/+55.0
Vibration Resistance Amplitude:
0.06 inches total excursion
Shock Resistance Rating In Gravitational Units:
30.0
Operating Tempurature Range:
+0.0/+50.0 degrees celsius
Average Life Measurement:
Not rated
End Application:
Jetds no. An/bqh- (v) 4, data gathering set
Basic Shape Style:
Rectangular or square
Identification Designator:
Co-636b-5 at 4mhz-27802
Inclosure Type:
Hermetically sealed
Installation Design:
Module
Circuit Construction Type:
Solid state
Frequency Per Channel:
4.0 megahertz output channel
Signal Voltage Rating Per Channel:
5.000 volts input and 15.000 volts input
Shock Pulse Duration Time:
11.0 milliseconds
Connection Type And Location:
Printed circuit bottom
Connection Contact Type And Quantity:
14 printed circuit external
External Dc Operating Voltage In Volts:
5.0 single voltage and 15.0 single voltage

## NSN 5955-01-151-1310

Crystal Controlled Oscillator - Page 2 of 2



_				-		
C	h	0	Iŧ.		ife:	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A32200