Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-151-1312

Overall Length:		
0.880 inches		
Overall Height:		
0.400 inches		
Overall Width:		
0.505 inches		
Environmental Protection:		
Shock resistant and vibration		
Vibration Resistance Range In Hertz:		
+1.0/+10.0		
Operating Tempurature Range:		
+0.0/+50.0 degrees celsius		
Average Life Measurement:		
Not rated		
End Application:		
5865-01-109-1686, controller, data link		
Basic Shape Style:		
Rectangular or square		
Identification Designator:		
Qt6t9m16mhz-51774		
Inclosure Type:		
Encased		
Operating Control Method:		
Manual		
Installation Design:		
Module		
Control Type:		
Local		
Circuit Construction Type:		
Solid state		
Frequency Per Channel:		
16.0 megahertz output channel		
Average Power Rating Per Channel:		
60.0 milliwatts output		
Signal Voltage Rating Per Channel:		
0.400 volts output and 2.400 volts output		
Connection Contact Type And Quantity:		
14 printed circuit external		
External Dc Operating Voltage In Volts:		
5.0 single voltage		
Shelf Life:		
N/a		

Crystal Controlled Oscillator - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

A32200