Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-151-9276

Overall Length: 0.800 inches Overall Height: 0.400 inches Overall Width:
Overall Height: 0.400 inches
0.400 inches
Overall Width:
0.500 inches
Environmental Protection:
Acid resistant and fungus proof and salt spray resistant and shock resistant and vibration
Operating Tempurature Range:
-55.0/+105.0 degrees celsius
Average Life Measurement:
Not rated
End Application:
Jetds type no. An/upx-24, interrogator set
Basic Shape Style:
Rectangular or square
Identification Designator:
Eros-200-5-20.98/10.49mhz-13571
Inclosure Type:
Hermetically sealed
Installation Design:
Module
Circuit Construction Type:
Solid state
Frequency Per Channel:
10.491295 megahertz output channel and 20.98259 megahertz output channel
Signal Voltage Rating Per Channel:
0.800 volts output and 2.400 volts output
Overall Gain:
30.0 milliamperes
Connection Type And Location:
Printed circuit bottom
Connection Contact Type And Quantity:
14 printed circuit external
External Dc Operating Voltage In Volts:
4.75 single voltage and 5.25 single voltage
Precious Material And Location:
External surfaces gold
Precious Material:
Gold
Shelf Life:
N/a

Crystal Controlled Oscillator - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A32200