## NSN 5955-01-153-7635

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-153-7635 **Overall Length:** 0.206 inches **Overall Diameter:** 0.505 inches **Environmental Protection:** Shock resistant and vibration **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Storage Tempurature Range:** -65.0/+125.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Cylindrical **Identification Designator:** Mcm677b-4.474mhz-51774 **Inclosure Type:** Hermetically sealed **Installation Design:** Module **Circuit Construction Type:** Solid state Frequency Per Channel: 4.474 megahertz output channel Signal Voltage Rating Per Channel: 2.400 volts output and 5.500 volts output **Overall Gain:** 60.0 milliamperes **Connection Type And Location:** Printed circuit bottom **Connection Contact Type And Quantity:** 6 printed circuit external **External Dc Operating Voltage In Volts:** 5.0 single voltage **Precious Material And Location:** Terminal surface gold **Precious Material:** Gold Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5955-01-153-7635

Crystal Controlled Oscillator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A32200