

View Online at <https://aerobasegroup.com/nsn/5955-01-154-3752>

Overall Length:

5.360 inches

Overall Height:

1.620 inches

Overall Width:

2.660 inches

Environmental Protection:

Shock resistant and vibration

Vibration Resistance Range In Hertz:

+4.0/+25.0

Vibration Resistance Amplitude:

0.12 inches total excursion and 0.10 inches total excursion

Shock Resistance Rating In Gravitational Units:

90.0

Operating Temperature Range:

-28.0/+75.0 degrees celsius

Average Life Measurement:

Not rated

Basic Shape Style:

Rectangular or square

Inclosure Type:

Encased

Installation Design:

Rack

Circuit Construction Type:

Solid state

Frequency Per Channel:

4435.0 megahertz operating channel

Frequency Adjustment Type:

Continuous

Signal Voltage Rating Per Channel:

28.000 volts input

Impedance Rating Per Channel:

50.000 ohms operating channel

Distortion Type And Percent:

3.0 frequency

Maximum Continuous Operating Time In Hours:

50.0

Shock Pulse Duration Time:

10.0 milliseconds

Connection Type And Location:

Connector, plug front and solder lug front

Connection Contact Type And Quantity:

1 connector, plug external and 3 solder lug external

External Dc Operating Voltage In Volts:

0.0 single voltage and 28.0 single voltage

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32200