

NSN 5955-01-155-9711 Crystal Controlled Oscillator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5955-01-155-9711 **Overall Length:** 1.000 inches **Overall Height:** 0.760 inches **Overall Width:** 1.000 inches **Environmental Protection:** Shock resistant and vibration **Vibration Resistance Range In Hertz:** +10.0/+500.0 **Vibration Resistance Amplitude:** 10.0 gravitational units **Shock Resistance Rating In Gravitational Units:** 200.0 **Operating Tempurature Range:** -55.0/+105.0 degrees celsius **Storage Tempurature Range:** -62.0/+125.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Maximum Operating Altitude Rating:** 12000.0 feet **Inclosure Type:** Encased **Operating Control Method:**

Automatic

Installation Design:

Module

Control Type:

Remote

Circuit Construction Type:

Solid state

Frequency Per Channel:

11.9917 megahertz operating channel

Shock Pulse Duration Time:

11.0 milliseconds

Connection Type And Location:

Pin bottom

Connection Contact Type And Quantity:

4 pin external

NSN 5955-01-155-9711

Crystal Controlled Oscillator - Page 2 of 2



External Dc Operating Voltage In Volts:

4.5 single voltage and 5.5 single voltage

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200