## NSN 5955-01-156-8871

Crystal Controlled Oscillator - Page 1 of 2



· ·	
View Online at https://aerobasegroup.com/nsn/5955-01-156-8871	
Overall Length:	
1.000 inches	
Overall Height:	
0.462 inches	
Overall Width:	
0.600 inches	
Environmental Protection:	
Shock resistant and vibration	
Vibration Resistance Range In Hertz:	
+5.0/+55.0	
Vibration Resistance Amplitude:	
0.06 inches total excursion	
Shock Resistance Rating In Gravitational Units:	
40.0	
Operating Tempurature Range:	
+0.0/+70.0 degrees celsius	
Storage Tempurature Range:	
-62.0/+75.0 degrees celsius	
Average Life Measurement:	
Not rated	
Basic Shape Style:	
Rectangular or square	
Identification Designator:	
K1091a-5.616128mhz-04713	
Inclosure Type:	
Hermetically sealed	
Operating Control Method:	
Manual	
Installation Design:	
Module	
Control Type:	
Local	
Circuit Construction Type:	
Solid state	
Frequency Per Channel:	

5.616128 megahertz output channel

**Average Power Rating Per Channel:** 

300.0 milliwatts output

**Signal Voltage Rating Per Channel:** 

0.400 volts output and 2.400 volts output

**Shock Pulse Duration Time:** 

11.0 milliseconds

## NSN 5955-01-156-8871

Crystal Controlled Oscillator - Page 2 of 2



Connection Type And Location:
Printed circuit bottom
Connection Contact Type And Quantity:
14 printed circuit external
External Dc Operating Voltage In Volts:
5.0 single voltage
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A32200