## NSN 5955-01-158-8732

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-158-8732 **Overall Length:** 0.887 inches **Overall Height:** 0.400 inches Overall Width: 0.540 inches **Environmental Protection:** Shock resistant and vibration Vibration Resistance Range In Hertz: +1.0/+10.0 **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Storage Tempurature Range:** -62.0/+125.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Inclosure Type:** Hermetically sealed **Operating Control Method:** Automatic Installation Design: Module **Circuit Construction Type:** Solid state Frequency Per Channel: 10.25 megahertz operating channel **Connection Type And Location:** Err-060 glad hand quick disconnect **Connection Contact Type And Quantity:** 14 liters of liquid nitrogen drain **External Dc Operating Voltage In Volts:** 4.5 single voltage and 5.5 single voltage **Test Data Document:** 81349-mil-o-55310 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Data:** 

N/a

Shelf Life:

**Unit Of Measure:** 

81349-mil-o-55310/16 government specification

## NSN 5955-01-158-8732

Crystal Controlled Oscillator - Page 2 of 2



Demilitarization:

No

Fiig:

A32200