NSN 5955-01-158-8744

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-158-8744 **Overall Length:** 0.815 inches **Overall Height:** 0.373 inches **Overall Width:** 0.515 inches **Environmental Protection:** Moisture proof and shock resistant and vibration **Vibration Resistance Range In Hertz:** +10.0/+2000.0 **Vibration Resistance Amplitude:** 20.0 gravitational units **Shock Resistance Rating In Gravitational Units:** 1000.0 **Operating Tempurature Range:** +0.0/+70.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Identification Designator:** M1145-16m-08111 **Inclosure Type:** Encased **Operating Control Method:** Automatic **Installation Design:** Module **Control Type:** Remote **Circuit Construction Type:** Solid state Frequency Per Channel: 16.0 megahertz operating channel **Shock Pulse Duration Time:** 0.35 milliseconds **Connection Type And Location:** Pin bottom **Connection Contact Type And Quantity:** 4 pin external

External Dc Operating Voltage In Volts:

4.5 single voltage and 5.5 single voltage

NSN 5955-01-158-8744

Crystal Controlled Oscillator - Page 2 of 2



	Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200