## NSN 5955-01-159-3529

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-159-3529 **Overall Length:** 0.890 inches **Overall Height:** 0.380 inches **Overall Width:** 0.530 inches **Environmental Protection:** Shock resistant and vibration **Vibration Resistance Range In Hertz:** +1.0/+10.0 **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Storage Tempurature Range:** -65.0/+125.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Identification Designator:** 930740-3b-82577 Inclosure Type: Hermetically sealed **Operating Control Method:** Manual **Installation Design:** Module **Control Type:** Local **Circuit Construction Type:** Solid state Frequency Per Channel: 1.024 megahertz output channel **Signal Voltage Rating Per Channel:** 2.400 volts output and 5.500 volts output **Overall Gain:** 60.0 milliamperes **Connection Type And Location:** Printed circuit bottom **Connection Contact Type And Quantity:** 14 printed circuit external **External Dc Operating Voltage In Volts:** 

5.0 single voltage

## NSN 5955-01-159-3529

Crystal Controlled Oscillator - Page 2 of 2



Precious	Material	And	Location:

Terminal surface gold

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A32200